

**CANTER**

CANTER

FE125

DELIVERING  
lower cost-of-ownership.



MITSUBISHI FUSO TRUCK OF AMERICA, INC.

# CANTER

# FE125

## SPECIFICATIONS (standard AC and AM/FM/CD player on all models)

A boost for your business and your bottom line. The Canter® will change the way you think about moving your company forward. Its cost-of-ownership is so low you can measure it by the mile—in dramatically improved fuel economy, service intervals, payload capacity and driver productivity. Its fuel-injected diesel engine and automated manual transmission set new benchmarks for efficiency and driving ease. They're backed by our industry-best 5-Year/175,000-Mile powertrain limited warranty. The Canter FE125. It's just the boost your business needs.



Weight ratings	GVWR/GCWR	12,500 lb./20,215 lb.		
	GAWR (front/rear)	5,360 lb./9,880 lb.		
Curb weight	Base model	5,225 lb. (est.)		
Body/Payload	Estimated max.	7,275 lb. (see dealer for details)		
Dimensions	Wheelbase	110.2"	133.9"	151.6"
	Overall length (cab/chassis)	204.1"	227.8"	245.5"
	Usable cab to rear axle	81.2"	104.9"	122.6"
	Body sizes accommodated	10' to 18'		
Engine	Model	4P10(T5)		
	Type	DOHC, 4-cylinder, 4-stroke cycle, water-cooled, turbocharged, intercooled diesel with 4 valves per cylinder		
	Displacement	183 cu. in. (3.0 L)		
	Max. output (SAE, gross)	161 hp @ 3,500 rpm		
	Max. torque (SAE, gross)	295 lb.-ft. @ 1,600 rpm		
Air cleaner	Type	Dry paper element with snorkel		
Transmission	Standard	Mitsubishi Fuso DUONIC® 6-speed OD AMT		
Axles	Front	5,735 lb.		
	Rear	9,925 lb.		
Final reduction gear	Type	Single-reduction hypoid		
	Ratio (std/opt'l)	4.875/5.285		
Top speed, est.	Std diff/Opt'l diff	90/83 mph		
Turning diameter	Shortest wheelbase	34.1'		
Tires (premium)	Configuration	Single front, dual rear		
	Size/Type	215/85R16 10PR: LR:E/All-season all positions		
Wheels	Size/Configuration	16" x 6"/5-lug		
Steering	Type	Ball-nut type with integral-type hydraulic power boost		
	Adjustments	Tilt/telescoping steering column with steering lock		
Suspension	Front	Laminated leaf springs with shock absorbers and stabilizer bar		
	Rear	Laminated leaf springs with shock absorbers		
Brakes	Service	Dual-caliper discs, vacuum/hydraulic-type with ABS		
	Parking	Drum/driveline, internal expanding shoe		
	Exhaust	Electrically actuated		
Frame	Type	Ladder/straight		
	Section modulus	7.08 cu. in. per rail		
	Yield strength	56,565 psi		
	RBM per rail	400,410 lb.-in.		
	Height/Width	32.5"/33.5"		
Fuel tank	Capacity/Location	30 gal./in-frame, aft of rear axle		
DEF tank	Capacity/Location	3.2 gal./right side		
Battery	Type/Capacity	Two 12-volt, maintenance-free/750 CCA		
Electrical	Starter/Alternator	12-volt/12-volt, 140A output		
Starting	Cold weather provision	Individual ceramic-tipped glow plugs		
Convenience	Windows/Door locks	Power-operated, one-touch up and down driver's-side window		
	Cruise control	Standard (programmable)		
	Entry	Keyless, with driver/assistant door lock control		

## SAFETY

Crush bar in each door, energy-absorbing steering column, daytime running lights, dual-caliper disc brakes with ABS (all wheels), covered open-grate entry steps, forward-swing doors for safer entry/exit, high-visibility halogen headlamps

## CAB COLORS

ARCADIA SILVER

NATURAL WHITE

JUPITER GREEN

MARS RED

SHANNON BLUE

SOLID BLACK

All models are available immediately in white. Other colors shown (except Solid Black) may be special-ordered at no extra charge. Accuracy of indicated hues is limited by paper/electronic reproduction.

## FABRIC STYLE

BLUE CLOTH

Vehicle specifications are subject to change without notice. Photos and descriptions included in this spec sheet may vary in comparison to actual vehicle models. For warranty limitations and details, see your local dealer.

PRINTED IN THE U.S.A. 4/12.  
©2012 MITSUBISHI FUSO TRUCK OF AMERICA, Inc.

**Mitsubishi Fuso Truck of America, Inc.**

2015 Center Square Road  
Logan Township, NJ 08085

[mitfuso.com](http://mitfuso.com)

